## JP2123114A2: PRODUCTION OF UNSATURATED RANDOM **COPOLYMER**

VDerwent Title:

Unsatd, random copolymers prodn, used for rubber rolls, belts, etc. - by polymerising alpha-olefin(s)! and non-conjugated diene! in presence of Ziegler-Natta catalyst [Derwent Record]

S Country:

JP Japan

\*Kind: A (See also: JP2682076B2)

KAWADA TAKASHI: ☑ Inventor:

**HIKITA MASAHIRO**; **MAKINO KENYA**;

\* Assignee:

**JAPAN SYNTHETIC RUBBER CO LTD** 

News, Profiles, Stocks and More about this company

♥ <u>Published / Filed</u>: 1990-05-10 / 1988-10-31

**Explication** JP1988000275232 <u>Number:</u>

FIPC Code: C08F 210/12; C08F 236/20;

Priority Number: 1988-10-31 JP1988000275232

S Abstract:

PURPOSE: To obtain the title copolymer capable of providing a cured rubber having low hardness and small compressive set by polymerizing α-olefin and non-conjugated diene compound having a specific structure at a specific ratio using a Ziegler-Natta catalyst.

CONSTITUTION: (A) 4-20C \u03c3-olefin (preferably hexene-1) is polymerized with (B) a non-conjugated diene compound (preferably 7-methyl-1,6-octadiene) expressed by the formula (n is 2-10; R1 is 1-8C alkyl; R2 and R3 are H or 1-8C alkyl) used so that content of the component B is 1-40mol%, in the presence of a Ziegler-Natta catalyst to provide the aimed copolymer. The polymerization temperature is preferably 20-60°C and polymerization pressure is ordinarily 0-20 atomic pressure. Furthermore. triethylaluminum or tributyl aluminum is preferably used as an organoaluminum compound constituting Ziegler-Natta catalyst.

COPYRIGHT: (C)1990, JPO& Japio

<u>View</u> Image

page

FEST AWAILABLE COPY